



## Luminaire Construction

**CNC machined from one of the following metals:**

### Aluminium

High corrosion resistant aluminium with chromate substrate and high UV polyester powder coat.

Body: 63.5 (2½") x 10mm (3/8").

Base: 63.5 (2½") solid aluminium tube.

Colours:

Black, Bronze, Corten, Dark Grey, Olive Green, Silver Star, White, White Birch.

### Copper

Body: 63.5mm (2½") x 10mm (3/8").

Base: 63.5 (2½") solid copper tube.

### 316 Stainless Steel

Body: 63.5mm (2½") x 10mm (3/8").

Base: 63.5 (2½") solid stainless steel tube.

## Mounting

For mounting on top of posts, railings, etc. This luminaire is not suited for ground installation.

## Features

### Lens

UV stable acrylic with anti-glare mesh projects light horizontally and at 45° onto the ground.

### Gasket

Silicone, iron impregnated 220°C (428°F).

### Lamp Holders

G4 - 350°C (662°F) ceramic multi contact lamp holder with 250°C (480°F) Teflon cables.


## Accessories

**Cable Joint Kit** (Cat. CJK150). Not approved for USA/Canada.

**Anti-Glare Hood** (Cat. HOOD140).

**Opaque Lens** (Cat. LENSBOLOP).

## Standards

IP66, UL1838, 

## Luminaire Weight

**Aluminium** - 0.370kg (13oz)

**Copper** - 0.600kg (1lb 5oz)

**Stainless Steel** - 0.500kg (1lb 1oz)

## Power Supply

Hunza Inground or Wall Mount Transformer: not included.

USA and Canada

Hunza Wall Mount Transformer: not included.

## Lamp Options

G4 - 20 watt lamp max.

USA and Canada

G4 - 20 watt lamp max.