

CNC machined from one of the following metals:

Aluminium

High corrosion resistant aluminium with chromate substrate and high resistant polyester powder coat.

Body: 63. mm 1 mm 3
End cap: solid aluminium 63. mm rod.

Bracket: 1 mm 1 3mm
1 aluminium flat bar.

Colours:

Black Bronze Corten Barre
Lilac Green Silver Star White
White Birch.

Copper

Body: 63. mm 1 mm 3
End cap: solid copper 63. mm rod.

Bracket: 1 mm 1 3mm
1 aluminium flat bar.

316 Stainless Steel

Body: 63. mm 1 mm 3
End cap: solid stainless steel 63. mm rod.

Bracket: 1 mm 1 3mm
1 aluminium flat bar.

Mounting

Via "U" bracket that is screwed to the mounting surface. If being used in a pond with a plastic liner then the weighted version should be used. No screws are required for fixing, therefore no leaks.

The luminaire may be mounted to a depth of 2 meters.

Note: Copper may not be suitable for use with fish.

Features

Lens

10mm (3/8") thick clear flush fit tempered shatter resistant glass. Lifetime Warranty.

Gaskets

Silicone, iron impregnated 220°C (428°F).

Lamp Holder

MR16 - 350°C (662°F) ceramic multi contact lamp holder with 250°C (480°F) Teflon cables.

Cable

1.3mm (16AWG) 3 meter (9") submersible cable. Longer cable available on request.

Accessories

Cable Joint Kit (Cat. CJK150). Not approved for USA/Canada.

Glare Guard (Cat. GG).

Hex Cell Louvre (Cat. HCL).

Frosted Lens (Cat. LENSSTEPF).

Standards

EN 0 P L



Luminaire

Luminaire 0.0 (1 oz)
Copper .00 (1 oz)
Stainless Steel .00 (1 oz)
Weighted version
Luminaire . (1 oz)
Copper .00 (1 oz)
Stainless Steel .0 (1 oz)

Power Supply

Hunza round or all mount
Transformer not included.

USA and Canada

Grounds welded earth transformer not included.

Luminaire

0 or 100 watt
USA and Canada
0 or 100 watt